



















































## KENGURUPARAOUTDOOREQUIPMENT

| No    | Image   | Description   | Price*EUR without VAT 21 % | Price*EUR with VAT 21%  |
|-------|---|---|----------------------------|---|
| P-001 |    | "PARAKENGURUParallelbars"The complex consists of four vertical columns and two parallel bars 1930mm in length. The distance between the inside surface of the parallel bars is 550mm. Construction is secured together with aluminium clamps.   | 755.20                     |    |
| P-002 |    | "PARAKENGURUClimb-downbars"The complex consists of two vertical columns and two climb-down bars 1930mm in height. Construction is secured together with aluminium clamps.   | 717.44                     |    |
| P-003 |    | "PARAKENGURUIncinedparallelbars"The complex consists of four vertical columns with different height and two inclined parallel bars 1790mm in length. The distance between the parallel bars is 608mm. Height difference for the parallel bars is 466,3mm. Construction is secured together with aluminium clamps.   | 880.28                     |    |
| P-004 |    | "PARAKENGURUCurvedparallelbars"The complex consists of four vertical columns and two parallel bars 1790mm in length. The distance between the parallel bars is 716mm. Construction is secured together with aluminium clamps.   | 792.96                     |    |
| P-005 |  | "PARAKENGURUParallelmulti-levelbars"The complex consists of four backup columns at the height of: 1400mm-2 pieces, 1100mm-2 pieces. Parallel bars are fixed to backup columns at the height 1100mm and 1400mm by means of collars. The distance between bars is 608mm, total length 1790mm, bar diameter 42mm. Weight-88.00kg.  | 818.92                     |  |
| P-006 |  | "PARAKENGURUParallelmulti-widthbars"The complex consists of four vertical columns and two multi-width parallel bars 1790mm in length. The distance between the parallel bars is 608mm at one end and 1008mm at the second end. Total width difference for the parallel bars is 400mm. Construction is secured together with aluminium clamps.                             | 783.52                     |  |
| P-007 |  | "PARAKENGURUIncinedMonkeybar"The complex consists of four vertical columns with different height and inclined monkey bar section 1790mm in length. Monkey bar section width is 1342,7mm. The distance between the cross bars of the monkey bar is 350mm. Height difference for the monkey bar section is 466,3mm. Construction is secured together with aluminium clamps. | 1253.16                    |  |
| P-008 |  | "PARAKENGURUParallelmulti-holdbars"The complex consists of two vertical columns and two multi-hold bars 413,7mm in height. The distance between the bars is 608mm. Construction is secured together with aluminium clamps.  | 625.40                     |  |

|       |   |  |         |   |
|-------|---|--|---------|---|
| P-009 |    | <p>"PARAKENGURU Various width parallel bars" The complex consists of four vertical columns and two bars 1790mm in length. The distance between the bars is 608mm at one end and 808mm at the second end. Total width difference for the bars is 200mm. Construction is secured together with aluminium clamps.</p>   | 741.04  |    |
| P-010 |    | <p>"PARAKENGURU Hammer bars" The complex consists of four vertical columns and two hammer bars 1790mm in length. Distance between the crossbars of the hammer bars is 380mm. The distance between the bars is 608mm. Construction is secured together with aluminium clamps.</p>   | 1208.32 |    |
| P-011 |    | <p>"PARAKENGURU Multi-level monkey bars" The complex consists of eight vertical columns of different height, two classic monkey bars, one inclined monkey bar and two climb-down bars with the length of 1930mm. The length of the classic monkey bars is 1900mm and the inclined monkey bar - 1790mm. The distance between the crossbars of classic monkey bars is 311mm, distance between the crossbars of inclined monkey bars is 350mm. Height difference for the inclined monkey bar section is 466, 3mm. Construction is secured together with aluminium clamps.</p> | 3551.80 |    |
| P-012 |   | <p>"PARAKENGURU MIN" The complex consists of six vertical columns of different height, one inclined monkey bar, one Swedish wall section, two crossbars 1200mm in length and two climb-down bars 1930mm in height. The length of inclined monkey bar - 1790mm. The distance between the crossbars of inclined monkey bars is 350mm. Height difference for the inclined monkey bar section is 466, 3mm. Construction is secured together with aluminium clamps.</p>   | 2990.12 |  |
| P-013 |  | <p>"Complex PARAKENGURU" The complex consists of fourteen vertical columns of different height, two crossbars 500mm in length, three crossbars 1200mm in length, one Swedish wall, two climb-down bars 1930mm in height, inclined parallel bars, multi-width parallel bars, multi-height parallel bars and a set of wooden bench. Height of the Swedish wall - 2073mm, width - 1200mm. The distance between the crossbars of the Swedish wall - 407mm. Construction is secured together with aluminium clamps.</p>   | 4769.56 |  |
| P-014 |  | <p>"Complex PARAKENGURU SUPER" The complex consists of twelve vertical columns of different height, three crossbars 500mm in length, four crossbars 1200mm in length, one Swedish wall, two climb-down bars 1930mm in height, monkey bar-snake, two hammer bars and a set of wooden bench for abs. Height of the Swedish wall - 2073mm, width - 1200mm. The distance between the crossbars of the Swedish wall - 407mm. Construction is secured together with aluminium clamps.</p>  | 5085.80 |  |
| P-015 |  | <p>"Complex PARAKENGURU LITE" The complex consists of twelve vertical columns of different height, three crossbars 500mm in length, four crossbars 1200mm in length, one Swedish wall, two climb-down bars 1930mm in height, monkey bar-snake, two hammer bars and a set of wooden bench for abs. Height of the Swedish wall - 2073mm, width - 1200mm. The distance between the crossbars of the Swedish wall - 407mm. Construction is secured together with aluminium clamps.</p>   | 2955.90 |  |

|       |   |   |         |   |
|-------|---|---|---------|---|
| P-016 |    | <p>"Complex PARAKENGURU NEW" The complex consists of eight vertical columns of different height, two crossbars 1200mm in length, two climb-down bars 1930mm in height, parallel bars and various width parallel bars. Construction is secured together with aluminium clamps.</p>   | 2419.00 |    |
| P-017 |    | <p>"Multi-height, multi-width parallel bars" The complex consists of six vertical columns of different height, multi-width parallel bars 1790mm in length and multi-height parallel bars 1790mm in length. The distance between the multi-width parallel bars is 608mm at one end and 1008mm at the second end. Total width difference for the parallel bars is 400mm. Height difference for the multi-height parallel bars is 200mm. Construction is secured together with aluminium clamps.</p>   | 1408.92 |    |
| P-018 |    | <p>"Complex PARAKENGURU MAX" The complex consists of thirteen vertical columns of different height, five crossbars 500mm in length, four crossbars 1200mm in length, one Swedish wall, two climb-down bars 1930mm in height, inclined parallel bars 1790mm in length and two sets of wooden bench. Height of the Swedish wall - 2073mm, width - 1200mm. The distance between the crossbars of the Swedish wall - 407mm. Construction is secured together with aluminium clamps.</p>   | 4685.78 |    |
| P-019 |  | <p>"Complex PARAKENGURU MEGA" The complex consists of twenty vertical columns of different height, two crossbars 500mm in length, three crossbars 1200mm in length, Swedish wall, two classic monkey bars, inclined monkey bar, two climb-down bars 1930mm in height, inclined parallel bars 1790mm in length, multi-width parallel bars 1790mm in length, multi-height parallel bars 1790mm in length and a set of wooden bench. Height of the Swedish wall - 2073mm, width - 1200mm. The distance between the crossbars of the Swedish wall - 407mm. The length of the classic monkey bars is 1900mm and the inclined monkey bar - 1790mm. The distance between the crossbars of classic monkey bars is 311mm, distance between the crossbars of inclined monkey bars is 350mm. Construction is secured together with aluminium clamps.</p> | 7629.88 |  |
| P-020 |  | <p>"Multi-width, inclined parallel bars" The complex consists of six vertical columns of different height, multi-width parallel bars 1790mm in length and inclined parallel bars 1790mm in length. The distance between the multi-width parallel bars is 608mm at one end and 1008mm at the second end. Total width difference for the parallel bars is 400mm. Height difference for the inclined parallel bars is 466,3mm. Construction is secured together with aluminium clamps.</p>   | 1470.28 |  |
| P-021 |  | <p>"Complex PARAKENGURU LONG" The complex consists of twelve vertical columns of different height, two crossbars 500mm in length, two crossbars 1200mm in length, inclined monkey bar, two climb-down bars 1930mm in height, inclined parallel bars 1790mm in length, multi-height parallel bars 1790mm in length and a set of wooden bench. The length of the inclined monkey bar - 1790mm. The distance between the crossbars of inclined monkey bars is 350mm. Construction is secured together with aluminium clamps.</p>   | 4100.50 |  |

|       |  |  |         |   |
|-------|--|--|---------|---|
| P-022 |   | <p>"Triple level monkey bars" The complex consists of eight vertical columns of different height, classic monkey bars and two inclined monkey bars. The length of the classic monkey bars is 1900mm and the inclined monkey bar - 1790mm. The distance between the crossbars of classic monkey bars is 311mm, distance between the crossbars of inclined monkey bars is 350mm. Construction is secured together with aluminium clamps.</p>   | 3122.28 |    |
| P-023 |   | <p>"Parallel multi-level bars with bench" The complex consists of six vertical columns of different height, two crossbars 500mm in length, multi-height parallel bars 1790mm in length and a set of wooden bench. The distance between the parallel bars is 608mm. Height difference for the parallel bars is 200mm. Construction is secured together with aluminium clamps.</p>   | 1467.92 |    |
| P-024 |   | <p>"Inclined parallel bars with bench" The complex consists of six vertical columns of different height, two crossbars 500mm in length, inclined parallel bars 1790mm in length and a set of wooden bench. The distance between the parallel bars is 608mm. Height difference for the parallel bars is 466,3mm. Construction is secured together with aluminium clamps.</p>  | 1529.28 |    |
| P-025 |  | <p>"Complex PARAKENGURUMEGA+" The complex consists of twenty one vertical columns of different height, four crossbars 500mm in length, five crossbars 1200mm in length, Swedish wall, two classic monkey bars, inclined monkey bar, two climb-down bars 1930mm in height, inclined parallel bars 1790mm in length, multi-height parallel bars 1790mm in length and two sets of wooden benches. Height of the Swedish wall - 2073mm, width - 1200mm. The distance between the crossbars of the Swedish wall - 407mm. The length of the classic monkey bars is 1900mm and the inclined monkey bar - 1790mm. The distance between the crossbars of classic monkey bars is 311mm, distance between the crossbars of inclined monkey bars is 350mm. Construction is secured together with aluminium clamps.</p> | 8143.18 |  |

**PRICE:**

The specified prices are denoted for the construction that have the original Kenguru Propowder paint RAL7016 and RAL2004 for the clamps. Other RAL colours are available, if needed. The cost for construction in other colours will be added to the final account individually. There is no extra cost for other colors for the clamps. The specified price does not include shipping cost. Shipping cost will be calculated for each order individually. The items will be shipped from Riga, Latvia.

**TECHNICAL PART:**

Column - steel pipe with a diameter of 108mm, thickness of wall not less than 3.2mm. Crossbar -

steel pipe with a diameter of 34mm, thickness of wall not less than 3.2mm. Crossbars and sections have installation holes under bolts M10.

Clamp - aluminium clamp for crossbar section fixation on vertical column. Clamp consists from two different pieces - one with holes, second with M10 threads and is tightened with two security bolts M10.

All vertical columns have plastic elliptical caps.